

# C140C

Media Converter

**10-100Mbps MM to SM 40km**

## Reliable, Stable and long life.

The Yamasaki C140C Media Converters convert Singlemode to Multimode and vice versa, they operate at 10 or 100Mbps.

The LED indicators show Multimode TX/RX, Singlemode TX/RX and power status.

Yamasaki C140C Media Converters have duplex SC connectors and a tough outer housing, providing excellent heat dissipation.

The Yamasaki C140C Media Converters can be used as a single stand alone unit or clustered in the Yamasaki R142 Rack Mount.

Recommended for use with:  
Yamasaki R142 Rack Mount 19" 2RU

## FEATURES

- Range Multimode: 2km
- Range Singlemode: 40km
- Wavelength Multimode 1310nm
- Wavelength Singlemode 1310nm
- Data Rate: 10 or 100Mbps
- Connectors: 2 x SC Duplex
- Complies with IEEE802.3u 100Base-FX standards
- External AC Adaptor
- Supports the transmission of extra-long VLAN packets
- Supports STP to form a redundant network
- Lifetime Warranty\*

Note. Some Yamasaki fiber optic laser products can cause eye damage if used incorrectly, Please consult your instruction manual and store away from children. Specifications and descriptions are subject to change without prior notice. \*Warranty 1 year on power supply.

[www.yamasakiot.com](http://www.yamasakiot.com)

To contact us, please email: [sales@yamasakiot.com](mailto:sales@yamasakiot.com)

DEPENDABILITY & RELIABILITY IN ONE NAME



**YAMASAKI**  
Optical Technology

