

C320C

Media Converter

Gigabit MM to SM 20km SC

Reliable, Stable and long life.

The Yamasaki C320C Media Converters convert Singlemode to Multimode and vice versa, they operate at 1000Mbps.

The LED indicators show Multimode TX/RX, Singlemode TX/RX and power status.

Yamasaki C320C Media Converters have duplex SC connectors and a tough outer housing, providing excellent heat dissipation.

The Yamasaki C320C Media Converters can be used as a single stand alone unit or clustered in the Yamasaki R142 Rack Mount.

Recommended for use with:
Yamasaki R142 Rack Mount 19" 2RU

FEATURES

- Range Multimode: 500m
- Range Singlemode: 20km
- Wavelength Multimode 850nm
- Wavelength Singlemode 1310nm
- Data Rate: 1000Mbps
- Connectors: 2 x SC Duplex
- Complies with IEEE 1000Base Standards
- External AC Adaptor
- Supports the transmission of extra-long VLAN packets
- Supports STP to form a redundant network
- Lifetime Warranty*

Note. Some Yamasaki fiber optic laser products can cause eye damage if used incorrectly, Please consult your instruction manual and store away from children. Specifications and descriptions are subject to change without prior notice. *Warranty 1 year on power supply.

www.yamasakiot.com

To contact us, please email: sales@yamasakiot.com

DEPENDABILITY & RELIABILITY IN ONE NAME



YAMASAKI
Optical Technology

