

# C420C

## Media Converter

### Gigabit Singlemode SC 20Km

#### Reliable, Stable and Smart.



The Yamasaki C420C Singlemode Media Converters are often used in pairs to convert a copper CAT5/5e/6 transmission to fiber optic transmission and back again, this can vastly increase the range of data networks. They operate bi-directionally at 1000 Mbps.

The Innovative LED indicators can display, data transfer rate, packet movement, connection status, full or half duplex and power status.

Yamasaki C420C Singlemode Media Converters have a strong aluminum outer housing, providing excellent heat dissipation and are useable stand alone or rack mountable.

Recommended for use with:

Yamasaki R142 Rack Mount 19" 2RU

#### FEATURES

- Range: 20 Kilometers
- Data Rate: 1000 Mbps
- Wavelengths: 1310nm
- Fiber Optic Connector: SC
- Fiber Type: Singlemode
- High Performance 1.4Gbps memory bandwidth
- Auto negotiation of straight through or crossover cables
- Full or Half Duplex operation modes
- Back Pressure Flow Control for both Full and Half duplex
- Supports QoS/VoIP packet transmission
- 6 smart LED Indicators
- Small space saving AC Adaptor
- Lifetime Warranty\*

Note. Some Yamasaki fiber optic laser products can cause eye damage if used incorrectly, Please consult your instruction manual and store away from children. Specifications and descriptions are subject to change without prior notice. \*warranty 1 year on power supply.

[www.yamasakiot.com](http://www.yamasakiot.com)

To contact us, please email: [sales@yamasakiot.com](mailto:sales@yamasakiot.com)

DEPENDABILITY & RELIABILITY IN ONE NAME



**YAMASAKI**  
Optical Technology