

YAMASAKI R142

Chassis for Media Converter



YAMASAKI
Optical Technology

Reliable, Stable and Smart.

The Yamasaki R142 Media Converter Chassis can hold up to 14 Yamasaki media converters, for ease of use it can handle hot swapping with any combination of different Yamasaki media converter models.

For maintaining perfect network stability, the Yamasaki R142 Media Converter Chassis comes with two built-in cooling fans, dual power supplies with smooth automatic switch-over.

Suitable for Yamasaki Media Converters.

Features:

- Dual Power Supplies
- Slots: 14
- LED Power indicators
- Hot Pluggable Slots
- Cabinet Size: 19" 2RU
- Circuit Breaker Protection



YAMASAKI R142

Model	R142
Form Factor	2RU19" Rack Mount Chassis
Media	Stand alone media converter
Operating Temperature	0°C~+70°C
Application	Network Communication
	FTTH / FTTB / FTTx
	ISP Backhaul Networking
Power in	AC220V Dual PWR Module
Power out	DC +5V, 12A
Relative Humidity	5%~95%
Slots	14 slots
Safety & Emission	CE, FCC, RoHS
Storage Temperature	-40°C~+85°C
Dimensions	422mm x230mm x90 mm;
	19 Inches 2U

Ordering Code:	Description:
Two models available to suit different power sources.	
R142	Media Converter AC 110V-240V
R142D	Media Converter DC-48V
C102C	Media Converter RJ45-MM/SC/2km/FE
C102T	Media Converter RJ45-MM/ST/2km/FE
C225C	Media Converter RJ45-SM/SC/25km/FE
C305C	Media Converter RJ45-MM/SC/500m/Gb
C420C	Media Converter RJ45-SM/SC/20km/Gb
C400	Media Converter RJ45 to SFP



YAMASAKI
Optical Technology

More information and details visit
www.yamasakiot.com

Specifications and descriptions are
subject to change without prior notice.

To contact us, please email:
sales@yamasakiot.com